
W7 0M5 4S P

12NC: 859991537000

GTIN (EAN) code: 8003437834349







Commercial code W7 0M5 Main colour of product Nere Construction type Built- Type of control Electro Type of control settings - Are any hobs controls integrated? Ne Which kind of hobs can be controlled? - Automatic programmes Ano Current (A) 16 Voltage (V) 220-2 Frequency (Hz) 50/6 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	MAIN FEATURES	
Main colour of product Construction type Built- Type of control Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Ano Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Sops Width of the product Sops Depth of the product Minimum niche height Nothed depth Nothed depth Nothed depth Nothed wight (kg) Usable volume (of cavity) Titlegrated Cleaning system Pyroly Grids of the cavity 2	Product group	0ven
Construction type Type of control Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Ano Current (A) Voltage (V) Tequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product System of the product Winimum niche height Online depth Net weight (kg) Usable volume (of cavity) Tight System Suilt- Telectro Type of control Electro Ano Ano Current (A) 16 220-22 50/6 220-22 50/6 220-22 50/6 220-22 50/6 200-20 50/6 200-20 50/6 200-20 50/6 200-20 50/6 200-20 50/6 200-20 50/6 200-20 50/6 200-20 50/6 50/6 50/6 50/6 50/6 50/6 50/6 50/	Commercial code	W7 0M5 4S P
Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Ano Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Sp5 Width of the product Sp5 Width of the product Sp5 Width of the product Sp6 Minimum niche height O Net weight (kg) Usable volume (of cavity) Tintegrated Cleaning system Pyroly Grids of the cavity 2	Main colour of product	Nerez
Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Net weight (kg) Usable volume (of cavity) Tintegrated Cleaning system Pyroly Grids of the cavity 2	Construction type	Built-in
Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Ano Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyroly Grids of the cavity 2	Type of control	Electronic
Which kind of hobs can be controlled? Automatic programmes Ano Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyroly Grids of the cavity 2	Type of control settings	-
Automatic programmes Current (A) 16 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyroly Grids of the cavity 2	Are any hobs controls integrated?	Ne
Current (A) 16 Voltage (V) 220-2 Frequency (Hz) 50/6 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Which kind of hobs can be controlled?	-
Voltage (V) 220-2 Frequency (Hz) 50/6 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Automatic programmes	Ano
Frequency (Hz) 50/6 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Current (A)	16
Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyroly Grids of the cavity 2	Voltage (V)	220-240
Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Frequency (Hz)	50/60
Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyroly Grids of the cavity 2	Length of Electrical Supply Cord (cm)	90
Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Plug type	Ne
Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Depth with open door 90 degree (mm)	-
Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Height of the product	595
Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Depth of the product	564
Niche depth 0 Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Minimum niche height	0
Net weight (kg) 40.5 Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Minimum niche width	0
Usable volume (of cavity) 73 Integrated Cleaning system Pyroly Grids of the cavity 2	Niche depth	0
Integrated Cleaning system Pyroly Grids of the cavity 2	Net weight (kg)	40.5
Grids of the cavity 2	Usable volume (of cavity)	73
,	Integrated Cleaning system	Pyrolytic
Trays 2	Grids of the cavity	2
	Trays	2

TECHNICAL FEATUR	ES
Timer	-
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Ano
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Grids
Probe of the cavity	Ne

ENERGETICKÝ ŠTÍTEK		
Energy input	Electric	
Type of energy of the cavity	Elektrický	
Energy efficiency class - NEW (2010/30/EU)	A+	
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.91	
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.7	