WF S2765 NE/IXL


12NC: 859991573720

GTIN (EAN) code: 8003437238567



SENSING THE DIFFERENCE





Product group Built-in Type of control Electronic Type of control Electronic Type of control Settings - Number of gas burners 0 Number of electric cooking zones 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Number of electric warming zones 0 Number of routrol panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 7200 Gas connection rating (W) 7200 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 54 Depth of the product 55 Depth of the product 56 Ninimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5 Automatic programmes	MAIN FEATURES	
Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Minimum niche height Minch weight (kg) Net weight (kg)	Product group	Hob
Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Basic surface material Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Minimum niche height Minicole or induction of the product induct induction of the product induct induction of the product induct induc	Construction type	Built-in
Number of gas burners 0 Number of electric cooking zones 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 54 Depth of the product 54 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Type of control	Electronic
Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 54 Depth of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Type of control settings	-
Number of electric plates 0 Number of radiant plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 54 Depth of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Number of gas burners	0
Number of radiant plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Number of electric cooking zones	0
Number of halogen plates 0 Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Number of electric plates	0
Number of induction plates 4 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Černá Electrical connection rating (W) 7200 Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Number of radiant plates	0
Number of electric warming zones Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) Net Tront Glass Front Front Front Front Front Front Front Front Basic surface material Glass MyA 0 0 0 0 0 N/A N/A 120 Plug type Ne Gas connection N/A Width of the product 54 Depth of the product 54 Depth of the product 510 Minimum niche width 560 Niche depth Net weight (kg) 10.5	Number of halogen plates	0
Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Minimum niche height Mich edepth Net weight (kg) Net requestion Front Glass Glass Front Glass Front Glass Front Glass N/A 0 0 0 0 0 0 0 0 0 0 0 0	Number of induction plates	4
Basic surface materialGlassMain colour of productČernáElectrical connection rating (W)7200Gas connection rating (W)0Gas typeN/ACurrent (A)31,3Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)120Plug typeNeGas connectionN/AWidth of the product650Height of the product54Depth of the product510Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)10.5	Number of electric warming zones	0
Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Solve (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Minimum niche height Miche depth Net weight (kg) Net veright (kg) Net veright (kg) To o Cerná Electrical Connection N/A Solve (V) 120 Plug type Ne 650 Ne 650 Minimum niche width 560 Niche depth A80 Net weight (kg)	Location of control panel	Front
Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 31,3 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) Ne 7200 7200 80 81,0 81,0 82 84 85 86 86 86 87 87 88 88 88 88 88	Basic surface material	Glass
Gas connection rating (W) 0 Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Main colour of product	Černá
Gas type N/A Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Electrical connection rating (W)	7200
Current (A) 31,3 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Gas connection rating (W)	0
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Gas type	N/A
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 120 Plug type Ne Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Current (A)	31,3
Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 120 Net Plug type Net Plug type Net Plug type N/A N/A Net Plug type N/A N/A N/A Net Plug type N/A N/A Net Plug type N/A N/A Net Plug type N/A N/A N/A N/A N/A N/A N/A N/	Voltage (V)	220-240
Plug type Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Net weight (kg)	Frequency (Hz)	50/60
Gas connection N/A Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Length of Electrical Supply Cord (cm)	120
Width of the product 650 Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Plug type	Ne
Height of the product 54 Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Gas connection	N/A
Depth of the product 510 Minimum niche height 28 Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Width of the product	650
Minimum niche height28Minimum niche width560Niche depth480Net weight (kg)10.5	Height of the product	54
Minimum niche width 560 Niche depth 480 Net weight (kg) 10.5	Depth of the product	510
Niche depth 480 Net weight (kg) 10.5	Minimum niche height	28
Net weight (kg) 10.5	Minimum niche width	560
5 (5)	Niche depth	480
Automatic programmes Ano	Net weight (kg)	10.5
	Automatic programmes	Ano

TECHNICAL FEAT	TURES
Power on indicator	Ano
Number of indicators	4
Type of regulation	Induction
Type of lid	Without
Residual heat indicator	Separate
Main on/off switch	Ano
Safety device	-
Timer	Ano

ENERGETICKÝ ŠTÍTEK	
Energy input	Electric