GOFL 629/S


12NC: 859991590720

GTIN (EAN) code: 8003437605277



SENSING THE DIFFERENCE





Product group Built-in Type of control Mechanical Type of control Mechanical Type of control Settings Knob Number of gas burners 4 Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Stříbrná Electrical connection rating (W) 0 Gas connection rating (W) 7800 Gas type C20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5 Automatic programmes	MAIN FEATURES	
Type of control Type of control settings Number of gas burners Number of electric cooking zones O Number of electric plates O Number of radiant plates O Number of halogen plates O Number of induction plates O Number of electric warming zones O Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type G20 Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Net weight (kg) Net weight (kg) Net weight (kg) Net weight (kg) Re O O O O O O O O O O O O O O O O O O	Product group	Hob
Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 12.5	Construction type	Built-in
Number of gas burners4Number of electric cooking zones0Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates0Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productStříbrnáElectrical connection rating (W)0Gas connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNeGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.5	Type of control	Mechanical
Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Stříbrná Electrical connection rating (W) 0 Gas connection rating (W) 7800 Gas type G20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Type of control settings	Knob
Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Stříbrná Electrical connection rating (W) 0 Gas connection rating (W) 7800 Gas type G20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Number of gas burners	4
Number of radiant plates 0 Number of induction plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Stříbrná Electrical connection rating (W) 0 Gas connection rating (W) 7800 Gas type G20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Number of electric cooking zones	0
Number of halogen plates0Number of induction plates0Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productStříbrnáElectrical connection rating (W)0Gas connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNeGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.5	Number of electric plates	0
Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Stříbrná Electrical connection rating (W) 0 Gas connection rating (W) 7800 Gas type G20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Number of radiant plates	0
Number of electric warming zones Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type G20 Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Net Stříbrná Glass Front Glass Avitable Avitable Avitable Front Glass Avitable Avitable Avitable Front Stříbrná Electrical connection avitable Avitable Front Stříbrná Front Stříbrná Avitable Avitable Front Stříbrná Avitable Avitable Front Avitable Avitable Front Avitable Avitable Front Stříbrná Avitable Avitable Front Avitable Avitable Front Avitable Avitable Avitable Front Stříbrná Avitable Avi	Number of halogen plates	0
Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type G20 Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Minimum niche height Minimum niche width Net weight (kg) Net results of control of the product Minimum niche width Minimum niche width Met weight (kg) Front Glass Front Glass Front Glass N/A 0 0 0 0 7800 820 220-240 Frequency (Hz) 50/60 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 510 Minimum niche width 560 Niche depth Net weight (kg) 12.5	Number of induction plates	0
Basic surface materialGlassMain colour of productStříbrnáElectrical connection rating (W)0Gas connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNeGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.5	Number of electric warming zones	0
Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Gurrent (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Reas connection N/A Width of the product Begin to perform the product Minimum niche height Minimum niche width Net weight (kg) Net veright (kg) Stříbrná Connection O,6 C20 Current (A) O,6 220-240 Frequency (Hz) 50/60 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 590 Minimum niche width 560 Niche depth Net weight (kg) 12.5	Location of control panel	Front
Electrical connection rating (W) Gas connection rating (W) Gas type G20 Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) O O O O O O O O O O O O O	Basic surface material	Glass
Gas connection rating (W) 7800 Gas type G20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Main colour of product	Stříbrná
Gas type G20 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Electrical connection rating (W)	0
Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Gas connection rating (W)	7800
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Gas type	G20
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Current (A)	0,6
Length of Electrical Supply Cord (cm) Plug type Sas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 85 Ne 85 N/A 86 Ne 87 89 Ne Ne 89 Ne Ne Ne Ne Ne Ne Ne Ne Ne N	Voltage (V)	220-240
Plug type Ne Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Frequency (Hz)	50/60
Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Length of Electrical Supply Cord (cm)	85
Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Plug type	Ne
Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Gas connection	N/A
Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Width of the product	590
Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.5	- ·	49
Minimum niche width 560 Niche depth 490 Net weight (kg) 12.5	Depth of the product	510
Niche depth 490 Net weight (kg) 12.5	Minimum niche height	41
Net weight (kg) 12.5	Minimum niche width	560
- 1 - 1	Niche depth	490
Automatic programmes Ne	Net weight (kg)	12.5
	Automatic programmes	Ne

TECHNICAL FEATURES		
Power on indicator	Ne	
Number of indicators	0	
Type of regulation	Semirapid	
Type of lid	Without	
Residual heat indicator	Without	
Main on/off switch	Ne	
Safety device	-	
Timer	Ne	

ENERGETICKÝ ŠTÍTEK	
Energy input	Plynová